

SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BLUE LABEL PASTE WAX (BROWN)
 PRODUCT NO: M860-12455
 RECOMMENDED USE: Furniture and Floor Wax
 COMPANY: RPM Wood Finishes Group
 2220 US Highway 70 SE, Ste 100
 Hickory, NC 28602
 Phone: 828-728-8266
 EMERGENCY TELEPHONE NUMBER: Chemtrec 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Danger
 Causes serious eye damage. Causes skin irritation. Harmful if swallowed or inhaled.

Wear protective gloves and eye protection. Wash thoroughly after handling. Do not eat drink or smoke when using this product. Avoid breathing spray. Use only outdoors or in a well-ventilated area.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.

If on skin: Take off contaminated clothing and wash it before reuse. Wash with plenty of water. If skin irritation occurs, get medical attention.

If swallowed: Rinse mouth. Call a doctor if you feel unwell.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

Dispose of contents/container in accordance with local/state/federal regulations.



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS #	WEIGHT %
Stoddard Solvent	8052-41-3	60-69%**
LPA Solvent	64742-47-8	10%
Carnauba Wax	8015-86-9	5-7%**
Paraffin Wax	8002-74-2	15-17%**

*Identity of this ingredient is a trade secret
 **Exact percentage of this ingredient is a trade secret

SECTION 4: FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.

If on skin: Take off contaminated clothing and wash it before reuse. Wash with plenty of water. If skin irritation occurs, get medical attention.

If swallowed: Rinse mouth. Call a doctor if you feel unwell.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

SECTION 5: FIRE FIGHTING MEASURES

TO AVOID SPONTANEOUS COMBUSTION soak soiled rags and other exposed items in a closed water filled metal container

EXTINGUISHING MEDIA: Use water spray, dry chemical, carbon dioxide or "alcohol" foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion may produce noxious and irritating gases which will require fresh air source in fire fighting.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear as a general precaution.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Use personal protective equipment; see Section 8.

Keep product from entering storm sewers and ditches that may lead to waterways.

Stop spill at source; dike and contain large spills and transfer to recovery container. Use absorbent for small spills and containerize.

See Section 13 for disposal.

SECTION 7: HANDLING AND STORAGE

Handle according to good manufacturing and warehousing practices. Avoid contact with eyes, skin and clothing.

Store indoors between 40F/4C and 100F/38C

Use product only for intended use. Follow label directions.

Wash hands after handling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT	CAS #	OSHA PEL (ppm or *mg.M ³) +=skin, c=ceiling	ACGIH TLV (ppm or *mg.M ³) +=skin, c=ceiling
Stoddard Solvent	8053-41-3	525 mg/m ³	N / A
LPA Solvent	64742-47-8	525 mg/m ³	N / A
Carnauba Wax	8015-86-9	N / A	N / A
Paraffin Wax	8002-74-2	2 mg / m ³	2 mg / m ³

EYES: Wear eye protection (i.e. chemical safety glasses with side shields or goggles). Contact lenses should not be worn.

SKIN: Chemical resistant clothing (i.e. gloves) is recommended.

RESPIRATORY PROTECTION: Not expected to be needed. Where over-exposure through inhalation may occur from use, approved respiratory protection equipment is recommended.

VENTILATION: Local exhaust or general room ventilation is normally adequate.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash station is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Brown Paste
ODOR: Mild solvent
ODOR THRESHOLD: NA
pH: N / A
MELTING/FREEZING POINT: Approx. 32F/0C
BOILING POINT: APPROX 320F/140C
BOILING RANGE: NA
FLASH POINT (CC): >105F/41C
EVAPORATION RATE: Approx. 0.21 (BuAc=1)
FLAMMABILITY: Not flammable nor combustible
UPPER/LOWER FLAMMABILITY LIMITS: 0.7 %
UPPER/LOWER EXPLOSIVE LIMITS: 6.0 %
VAPOR PRESSURE: 2.0 mmHg
VAPOR DENSITY: 4.7
RELATIVE DENSITY: 6.8 LB/GAL
SOLUBILITY: Insoluble in Water
PARTITION COEFFICIENT: N-OCTANOL/WATER: NA
AUTO-IGNITION TEMPERATURE: 260C
DECOMPOSITION TEMPERATURE: NA
VISCOSITY: N / A

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Stable
CHEMICAL STABILITY: Stable
POSSIBILITY OF HAZARDOUS REACTIONS: Low.
INCOMPATIBLE MATERIALS: Avoid acids, oxidizers and reducers.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and other gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Stoddard Solvent 8052-41-3

Ingestion LD Rat: > 5000 mg/kg

Dermal LD 50 Rabbit: > 3000 mg /kg

Turpentine 8006-64-2

Ingestion LD Rat: > 5000 mg/kg

Dermal LD 50 Rabbit: No Data Available

SECTION 12: ECOLOGICAL INFORMATION

Ecological data for this chemical mixture is not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local environmental regulations.

SECTION 14: TRANSPORT INFORMATION

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT < 5.0 Kg	1325	Flammable Solid n.o.s.	4.1	PG 111	No UN Shipping Docs	-
DOT > 5 Kg	1325	Flammable Solid n.o.s	4.1	PF 111	Flammable Solid Label	UN Packaging

SECTION 15: REGULATORY INFORMATION

TSCA Inventory Status: All components of this material are listed on the US Toxic Substances Control Act (TSCA) Inventory

SARA 311 / 312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health	No
Fire Hazard	Yes
Sudden Release	No
Reactive Hazard	No

SECTION 16: OTHER INFORMATION

Prepared: January 2, 2015

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which maybe the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer or his agent based on its own studies and on the work of others. Neither the manufacturer nor his agent makes any warranty, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. Neither the manufacturer nor his agent shall be held liable (regardless of fault) to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information. Data is supplied for use only in connection with occupational safety and health.