



SCRATCH OFF™ MAHOGANY

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M107-0381

SCRATCH OFF™ MAHOGANY

PRODUCT DESCRIPTION:

Scratch-Off™ Hide scratches and minor imperfections as you polish. Use on new or used furniture, woodwork, doors and paneling. Often used by manufacturers to hide residue in carvings after rubbing. Adds value. Net Wt. 13 oz.

ADVANTAGES:

1. Easy to use.
2. HIDES SCRATCHES • CLEANS • PROTECTS
3. Aerosol form – no extra equipment needed.
4. To be used sparingly

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	Brown
Sheen	N/A
Viscosity	N/A
WPG	6.262476182 lbs/gal
Solids by Volume	1.871600341 ±1%
Solids by Weight	2.611690306 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	730.786612773 g/l
Coating VOC (Lb/Gal)	6.098731601 lbs/gal
Material VOC (g/l)	730.786612821 g/l
Material VOC (Lb/Gal)	6.098731601 lbs/gal
#VOC/#Solid	37.289379035 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	2.906528844
Spread Rate	30.020469470 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Hydrotreated Heavy Alkanes - CAS 64742-52-5 - solvent
Petroleum Gases, Liquefied, Sweetened - CAS 68476-86-8 - propellant
C9-12 Light Alkanes - 64742-88-7 - solvent
Hydrotreated Light Alkanes - CAS 64742-47-8 - solvent
Toluene - CAS 108-88-3 - solvent
Asphalt, oxidized - CAS 64742-93-4 - colorant
m-Xylene - CAS 108-38-3 - solvent
Proprietary Resin - CAS not available - resin
2-Naphthalenecarboxamide, 4-[[4-(aminocarbonyl)phenyl]azo]-3-hydroxy-N-(2-methoxyphenyl)- CAS 36968-27-1 - colorant
o-Xylene - CAS 95-47-6 - solvent
p-Xylene - CAS 106-42-3 - solvent
2,4-Bis[(Dimethylphenyl)Azo]-1,3-Benzenediol - CAS 29190-28-1 - colorant
Lecithins, soya - CAS 8030-76-0 - emulsifier
Benzene - CAS 71-43-2 - not intentionally added
Dinonylnaphthalenesulfonic Acid - CAS 25322-17-2 - anti-static
Proprietary Anti-Static - CAS not available - anti-static

DIRECTIONS:

SHAKE WELL BEFORE USING. Apply to the surface, then wipe dry with a clean cloth and return the original finish to your furniture in minutes. Clean spray button immediately after use by turning can upside down and pressing spray button for 5 seconds or until no more product comes out.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.