



LEATHER REPAIR COLOR ADJUSTER - BLACK

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M109-4007	LEATHER REPAIR COLOR ADJUSTER - BLACK

PRODUCT DESCRIPTION:

Mohawk Leather Repair Color Adjusters are lightly pigmented colorants using very fine ground pigments, which will apply transparent color. Use according to color theory to fine-tune the color of the repair. The Leather Repair Aerosols are used to color over damages on pigmented leather (also known as top coated) where there is color loss or the leather has been repaired. The aerosols are designed to enable you to match most of the leather furniture that is popular today. They are especially effective at repairing two-tone finishes which are otherwise so difficult to match. The kit includes Basecoats for matching background colors, Toners to add color over the Basecoats and to apply the stippled effect in two-tones, Color Adjusters for fine-tuning the color of the repair, and Leather/Vinyl Finish™ to adjust the sheen.

ADVANTAGES:

- ▮ Transparent color – lightly pigmented
- ▮ Use to alter the hue of the Basecoat and Toner aerosols
- ▮ Blends the color during the repair process and/or the color of the final repair
- ▮ Uses color theory to work effectively

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Pigmented Leather Lacquer
Color	Black
Sheen	40-50
Viscosity	22-25 seconds in Zahn 1 @ 77F
WPG	6.176665104 lbs/gal
Solids by Volume	2.004404096 ±1%
Solids by Weight	3.176312835 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	668.038991345 g/l
Coating VOC (Lb/Gal)	5.575076874 lbs/gal
Material VOC (g/l)	420.695924911 g/l
Material VOC (Lb/Gal)	3.510890727 lbs/gal
#VOC/#Solid	17.895341451 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	1.170355996
Spread Rate	32.150390177 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	To recoat: 8 minutes To touch: 8 minutes To pack: 1 hour
Oven Dry	Not recommended
Shelf-Life (Unopened)	36 months

Pot-Life (Catalyzed)	N/A
Recoat Instruction	Air dry at least 8 minutes, do not force dry
PH	N/A

DIRECTIONS:

Transparent color coating used to finely tune the color of Leather Repair Basecoat and/or Leather Repair Toner aerosols to match the leather more precisely. SHAKE WELL. Use principles of color theory to pick the appropriate Leather Repair Color Adjuster and apply very lightly until the color of the leather is matched. Do not force dry. Clean spray button immediately by spraying with can upside down until no more product comes out. If clogged, remove spray button with a twisting motion and clean. Gently twist button onto can with opening turned away from you.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.