



# WOOL-LUBE RUBBING LUBRICANT PASTE GAL

## TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M720-1356,M720-1357	WOOL-LUBE RUBBING LUBRICANT PASTE GAL

### PRODUCT DESCRIPTION:

Wool-Lube paste is a highly concentrated, multi-purpose, water reducible, non-abrasive rubbing and sanding lubricant. Wool-Lube is non-toxic and contains no silicones. Reduce with water as a lubricant with steel wool or abrasive pads for smoothing, removing packing marks and scratches from finished surfaces. Wool-Lube is an excellent sanding lubricant for use with wet/dry sandpapers. Does not interfere with the adhesion or drying of lacquer. Finishes rubbed with Wool-Lube and an abrasive can be recoated immediately after being wiped dry. Can be used with dry abrasive powders such as Pumice Stone, Rotten Stone. Use of a sanding lubricant greatly extends the life of waterproof sandpapers.

### ADVANTAGES:

1. Easy to use.
2. Will not gum up.
3. Wipes clean.
4. Can be lacquered over.

### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base lubricant
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.345170000 lbs/gal
Solids by Volume	39.800000000 ±1%
Solids by Weight	39.800000000 ±1%
Flash Point	0.000000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	0.000000000 g/l
Coating VOC (Lb/Gal)	0.000000000 lbs/gal
Material VOC (g/l)	0.000000000 g/l
Material VOC (Lb/Gal)	0.000000000 lbs/gal
#VOC/#Solid	0.000000000 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	638.392000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A

---

PH

N/A

---

Water 7732-18-5 - solvent

Fatty acids, vegetable-oil, potassium salts - CAS 61788-65-6 - lubricant

---

**DIRECTIONS:**

Place a small amount of Mohawk Wool-Lube on a pad of 3/0 or 4/0 steel wool. Dip into water to wet pad; rub surface in the direction of the grain using smooth, even strokes, to obtain a uniform finish. For fine satin sheens, wet rub with 400-600 grit sandpaper and Mohawk Wool-Lube. No polish is necessary after Wool-Lube rubbing - simply wipe with a clean dry cloth.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.