



BRISTOL CREAM POLISH UNLABELED

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

KMP,M810-2002,M810-2004 BRISTOL CREAM POLISH UNLABELED
,M810-2004PLLH,M810-200
5,M810-2005IM,M810-2007,
U810-2004,U810-2005

PRODUCT DESCRIPTION:

Bristol® Cream Polish cleans and polishes interior wood finishes, plastic, enamel and porcelain and creates a hard, rich, clear protective finish.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Polish
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.005873162 lbs/gal
Solids by Volume	8.269836800 ±1%
Solids by Weight	9.490885924 ±1%
Flash Point	255.200000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	770.026440161 g/l
Coating VOC (Lb/Gal)	6.426194073 lbs/gal
Material VOC (g/l)	441.047935564 g/l
Material VOC (Lb/Gal)	3.680732946 lbs/gal
#VOC/#Solid	4.844164135 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000750784
Spread Rate	132.648053102 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	2.35

Hydrotreated Heavy Alkanes - CAS 64742-52-5 - luster/shine
Water - CAS 7732-18-5 - solvent
Polyethylene Glycol Branched Nonylphenyl Ether Phosphates - CAS 68412-53-3 - surfactant
Pine Essential Oil - CAS 8002-09-3 - lubricant, fragrance
Dinonylnaphthalenesulfonic Acid - CAS 25322-17-2 - anti-static
Proprietary Anti-Static - CAS not available - anti-static
Benzene - CAS 71-43-2 - not intentionally added

DIRECTIONS:

SHAKE WELL BEFORE USING. Dampen cloth with water and squeeze dry. Apply polish to cloth and apply surface. Wipe dry and buff with a clean cloth. Polish may also be dispersed in water to use for light dusting, 4 parts water to 1 part polish. Saturate cloth, squeeze dry, clean and polish. Follow by wiping with a clean dry cloth.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.