



PLASTIC POLISH HIGH GLOSS

TECHNICAL DATA SHEET

PRODUCT NUMBER

M810-4004

DESCRIPTION

PLASTIC POLISH HIGH GLOSS

PRODUCT DESCRIPTION:

Plastic Polish is used for plastic type substrates typically used to create pens and other projects.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base polish
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	10.873993800 lbs/gal
Solids by Volume	32.246301479 ±1%
Solids by Weight	48.000484762 ±1%
Flash Point	0.000000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	3.908057091 g/l
Coating VOC (Lb/Gal)	0.032614433 lbs/gal
Material VOC (g/l)	1.265024771 g/l
Material VOC (Lb/Gal)	0.010566109 lbs/gal
#VOC/#Solid	0.002022615 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000006986
Spread Rate	517.230675723 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

DIRECTIONS:

Shake well before using. Sand part on the lathe through the necessary, normal grit progression to level the surface before polishing, to at least 800 grit. Apply a small amount to a soft cloth or lint free paper towel and apply to the turning at a slow speed in an even end to end motion. Use a clean soft cloth or lint free paper towel to remove remaining residue. Repeat until desired gloss is achieved.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.