



SCRATCH OFF FOR LIGHT FINISHES 8 OZ

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M638-2321,M840-4002,M840-4004,M840-4005,M840-4007
SCRATCH OFF FOR LIGHT FINISHES 8 OZ

PRODUCT DESCRIPTION:

MOHAWK SCRATCH-OFF™ FOR LIGHT FINISHES is perfect for antiques and other interior woodwork. Use to hide minor scratches and revive or polish the finish of light colored woods such as Ash and other natural light woods.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.235070343 lbs/gal
Solids by Volume	0.456079010 ±1%
Solids by Weight	0.508084557 ±1%
Flash Point	120.200000000 °F
HMIS	H: 0, F: 2, R: 0, P: X
Coating VOC (g/l)	862.544701505 g/l
Coating VOC (Lb/Gal)	7.198310062 lbs/gal
Material VOC (g/l)	862.544701489 g/l
Material VOC (Lb/Gal)	7.198310062 lbs/gal
#VOC/#Solid	195.817633631 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.780166226
Spread Rate	7.315507320 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Hydrotreated Heavy Alkanes - CAS 64742-52-5 - solvent
C8-9 Alkane/Cycloalkane - CAS 64742-49-0 - solvent
C9-12 Light Alkanes - CAS 64742-88-7 - solvent
Hydrotreated Light Alkanes - 64742-47-8 - solvent
Proprietary Fragrance - CAS not available - fragrance
Toluene - CAS 108-88-3 - solvent

Chromate(1-), bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]-, hydrogen - CAS 5601-29-6 - colorant
Benzene - CAS 71-43-2 - not intentionally added
Dinonylnaphthalenesulfonic Acid - CAS 25322-17-2 - anti-static
Proprietary Anti-Static - CAS not available - anti-static

DIRECTIONS:

SHAKE WELL BEFORE USING. Apply Scratch-Off™ to a soft cloth. Wipe evenly over the entire surface. Wipe dry with another cloth.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.