



8XOZ POLISH QT

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M860-0005,M860-0006,M86 8XOZ POLISH QT
0-0007,M860-0009,MC860-0
006,U860-0002

PRODUCT DESCRIPTION:

CLEANS, PROTECTS AND POLISHES all enameled, varnished and lacquered wood or metal surfaces, leather, linoleum, tile, glass, porcelain, masonite. EXCELLENT FOR: Venetian Blinds, Bathroom Fixtures, Windows, Mirrors, Furniture, Pianos, Woodwork, All Kitchen Appliances.

ADVANTAGES:

1. Antistatic agent for less dusting
2. Ultraviolet light absorber to protect the color of the wood
3. Contains no silicones
4. Lemon scent for a fresh, clean fragrance
5. Extended evaporation rate meaning larger pieces can be polished with greater ease

Limitations

1. Keep from freezing
2. Do not use on lo-gloss or flat sheen surfaces
3. Designed for interior use only
4. Not suitable for high temperature areas

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Polish
Color	Clear - Polish
Sheen	N/A
Viscosity	18-23 seconds Signature Zahn 3 @ 77F
WPG	7.769658695 lbs/gal
Solids by Volume	21.242024862 ±1%
Solids by Weight	18.005621968 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 1, R: 0, P: X
Coating VOC (g/l)	522.623961765 g/l
Coating VOC (Lb/Gal)	4.361523891 lbs/gal
Material VOC (g/l)	266.508204996 g/l
Material VOC (Lb/Gal)	2.224126692 lbs/gal
#VOC/#Solid	1.589825479 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	340.722078786 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months

Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	7.5
Contains UV Absorber	
Water - CAS 7732-18-5 - solvent Castor oil, oxidized - CAS 68187-84-8 - luster/shine Hydrotreated Light Alkanes - CAS 64742-47-8 - solvent Solvent naphtha, petroleum, heavy aliphatic - CAS 64742-96-7 - solvent Hydrotreated Middle Alkanes - CAS 64742-46-7 - solvent Mineral Oil - CAS 8042-47-5 - luster/shine Proprietary Oil - CAS not available - luster/shine Secondary Alcohol Ethoxylate - CAS 84133-50-6 - surfactant Xanthan Gum - CAS 11138-66-2 - rheology Proprietary Fragrance - CAS not available - fragrance Sodium Hydroxide - CAS 1310-73-2 - pH adjustment Benzophenone-4 - CAS 4065-45-6 - UV absorber 1-Propanaminium, 3-(dodecyloxy)-2-hydroxy-N,N-bis(2-hydroxyethyl)-N-methyl-, methyl sulfate (salt) - CAS 18602-17-0 - anti-static	

DIRECTIONS:

SHAKE WELL. Clean and wipe surfaces well. Pour a small quantity of polish on a clean, soft, lint-free cloth and apply in the conventional manner. For stainless steel and formica, apply with dampened sponge. USE SPARINGLY. OZ® does not require excessive rubbing - the surface brightens immediately and will not show finger marks. Previously waxed and oil polished surfaces can cause smudging because of build up. If so, remove with mild detergent and warm water before applying OZ®. Keep from freezing and do not apply to flat painted surfaces.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.