

BACKGROUND MARKER TOUCH-UP EVERGREEN FOG SWP

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M294-0384

BACKGROUND MARKER TOUCH-UP EVERGREEN FOG SWP

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

TechnologyN/AColorGREENSheenN/AViscosityN/AViscosity9.125149627 lbs/galSolids by Volume29.573973436 ±1%Solids by Weight46.859118321 ±1%Flash Point55.4000000 °FHMISH: 2, F: 3, R: 0, P: XCoating VOC (g/l)579.564910143 g/lCoating VOC (g/l)579.564910143 g/lCoating VOC (b/Gal)4.836720830 lbs/galMaterial VOC (g/l)578.412790854 g/lMaterial VOC (g/l)1.28892841 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004816614Spread Rate474.36633913 sq. ft/gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/AAlcringN/AAlcringN/ASpread RateN/AAlcringN/AFeducerN/AFurdir (Unopened)36 monthsPieLLife (Unopened)N/APieLLife (Catalyzed)N/AFeducatinstructionN/A		
SheenN/AViscosityN/AWPG9.125149627 lbs/galSolids by Volume29.573973436 ±1%Solids by Weight46.859118321 ±1%Flash Point55.4000000 °FHMISH: 2, F: 3, R: 0, P: XCoating VOC (g/l)579.564910143 g/lCoating VOC (g/l)578.412790854 g/lMaterial VOC (g/l)578.412790854 g/lMaterial VOC (Lb/Gal)4.827105894 lbs/gal#VOC/#Solid1.12889241 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004818614Spread RateVI/AReducerN/AReducerN/AAirDryN/AOven DryN/ASheff-Life (Unopened)36 monthsPot-Life (Catalyzed)N/APot-Life (Catalyzed)N/ARecoat InstructionN/A	Technology	N/A
Viscosity N/A WPG 9.125149627 lbs/gal Solids by Volume 29.573973436 ±1% Solids by Weight 46.859118321 ±1% Flash Point 55.4000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 579.564910143 g/l Coating VOC (b/Gal) 4.836720830 lbs/gal Material VOC (g/l) 578.412790854 g/l Material VOC (b/Gal) 4.827105894 lbs/gal #VOC/#Solid 1.128892841 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.004818614 Spread Rate 474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Pot-Life (Catalyzed) N/A	Color	GREEN
WPG 9.125149627 lbs/gal Solids by Volume 29.573973436 ±1% Solids by Weight 46.859118321 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 579.564910143 g/l Coating VOC (b/Gal) 4.836720830 lbs/gal Material VOC (g/l) 578.412790854 g/l Material VOC (b/Gal) 4.827105894 lbs/gal #VOC/#Solid 1.128892841 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.004818614 Spread Rate 474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Pot-Life (Catalyzed) N/A	Sheen	N/A
Solids by Volume 29.573973436 ±1% Solids by Weight 46.859118321 ±1% Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 579.564910143 g/l Coating VOC (g/l) 578.412790854 g/l Material VOC (g/l) 578.412790854 g/l Material VOC (g/l) 578.412790854 g/l Material VOC (g/l) 578.412790854 g/l VAPR Ratio (#VHAP/#Solid) 0.004818614 Spread Rate 474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A	Viscosity	N/A
Solids by Weight 46.859118321 ±1% Flash Point 55.4000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 579.564910143 g/l Coating VOC (Lb/Gal) 4.836720830 lbs/gal Material VOC (g/l) 578.412790854 g/l Material VOC (Lb/Gal) 4.827105894 lbs/gal #VOC/#Solid 1.128892841 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.004818614 Spread Rate 474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A	WPG	9.125149627 lbs/gal
Flash Point 55.40000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 579.564910143 g/l Coating VOC (Lb/Gal) 4.836720830 lbs/gal Material VOC (g/l) 578.412790854 g/l Material VOC (Lb/Gal) 4.827105894 lbs/gal #VOC/#Solid 1.128892841 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.004818614 Spread Rate 474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A	Solids by Volume	29.573973436 ±1%
HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 579.564910143 g/l Coating VOC (Lb/Gal) 4.836720830 lbs/gal Material VOC (g/l) 578.412790854 g/l Material VOC (Lb/Gal) 4.827105894 lbs/gal #VOC/#Solid 1.128892841 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.004818614 Spread Rate 474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Rectarting N/A	Solids by Weight	46.859118321 ±1%
Coating VOC (g/l)579.564910143 g/lCoating VOC (Lb/Gal)4.836720830 lbs/galMaterial VOC (g/l)578.412790854 g/lMaterial VOC (Lb/Gal)4.827105894 lbs/gal#VOC/#Solid1.128892841 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004818614Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecot InstructionN/A	Flash Point	55.40000000 °F
Coating VOC (Lb/Gal)4.836720830 lbs/galMaterial VOC (g/l)578.412790854 g/lMaterial VOC (Lb/Gal)4.827105894 lbs/gal#VOC/#Solid1.128892841 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004818614Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/AN/A	HMIS	H: 2, F: 3, R: 0, P: X
Material VOC (g/l)578.412790854 g/lMaterial VOC (Lb/Gal)4.827105894 lbs/gal#VOC/#Solid1.128892841 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004818614Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/AN/A	Coating VOC (g/I)	579.564910143 g/l
Material VOC (Lb/Gal)4.827105894 lbs/gal#VOC/#Solid1.128892841 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004818614Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/AN/A	Coating VOC (Lb/Gal)	4.836720830 lbs/gal
#VOC/#Solid1.128892841 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.004818614Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/AN/A	Material VOC (g/l)	578.412790854 g/l
VHAP Ratio (#VHAP/#Solid)0.004818614Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Material VOC (Lb/Gal)	4.827105894 lbs/gal
Spread Rate474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	#VOC/#Solid	1.128892841 lbs/lbs solid
Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	VHAP Ratio (#VHAP/#Solid)	0.004818614
ReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Spread Rate	474.366533913 sq. ft./gal @ 1.0 mil DFT (no loss)
RetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Catalyst/Ratio	N/A
AirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Reducer	N/A
Oven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Retarder	N/A
Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.