

ENDURAGREEN INTERIOR ACRYLIC WHITE SEMI-GLOSS 60 SHEEN 5 GA

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M640-41608

ENDURAGREEN INTERIOR ACRYLIC WHITE SEMI-GLOSS 60 SHEEN 5 GA

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Waterborne Acrylic	
Color	White	
Sheen	60 +/- 3 @ 4 wet mils applied	
Viscosity	15-20 #3 Zahn Cup	
WPG	9.655117927 lbs/gal	
Solids by Volume	26.742378667 ±1%	
Solids by Weight	36.606076661 ±1%	
Flash Point	0.00000000 °F	
HMIS	H: 2, F: 1, R: 0, P: X	
Coating VOC (g/l)	137.504949718 g/l	
Coating VOC (Lb/Gal)	1.147538512 lbs/gal	
Material VOC (g/l)	43.348830243 g/l	
Material VOC (Lb/Gal)	0.361764811 lbs/gal	
#VOC/#Solid	0.102356530 lbs/lbs solid	
VHAP Ratio (#VHAP/#Solid)	0.000425746	
Spread Rate	428.947753819 sq. ft./gal @ 1.0 mil DFT (no loss)	
Catalyst/Ratio	N/A	
Reducer	Water if needed	
Retarder	Up to 4 oz/Gal 745-700 if needed for open time	
AirDry	30 Minutes to sand	
Oven Dry	Customer specific	
Shelf-Life (Unopened)	12 months	
Pot-Life (Catalyzed)	N/A	
Recoat Instruction	Dry 1 hour minimum, scuff sand with 320 grit prior to recoat.	
PH	8.2	

1 freeze/thaw cycle. If product freezes, allow 48 to 72 hours to recover.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.