

# WOOD TURNERS FRICTION POLISH

## TECHNICAL DATA SHEET

| PRODUCT NUMBER | DESCRIPTION                  |
|----------------|------------------------------|
| M810-3004      | WOOD TURNERS FRICTION POLISH |

#### PRODUCT DESCRIPTION:

Wood Turner's Friction Polish is commonly applied to natural wood turnings and creates sheen by quickly and easily burnishing or polishing the natural wood to high gloss lusters.

### PHYSICAL PROPERTIES AND SPECIFICATIONS

| Technology                | Solvent base polish                               |
|---------------------------|---|
| Color                     | N/A   |
| Sheen                     | N/A   |
| Viscosity                 | N/A   |
| WPG                       | 7.412477978 lbs/gal                               |
| Solids by Volume          | 27.062023096 ±1%                                  |
| Solids by Weight          | 35.105557425 ±1%                                  |
| Flash Point               | 55.400000000 °F                                   |
| HMIS                      | H: 2, F: 3, R: 0, P: X                            |
| Coating VOC (g/I)         | 575.563352490 g/l                                 |
| Coating VOC (Lb/Gal)      | 4.803326094 lbs/gal                               |
| Material VOC (g/l)        | 574.417146751 g/l                                 |
| Material VOC (Lb/Gal)     | 4.793760509 lbs/gal                               |
| #VOC/#Solid               | 1.842201128 lbs/lbs solid                         |
| VHAP Ratio (#VHAP/#Solid) | 0.00000000  |
| Spread Rate               | 434.074850460 sq. ft./gal @ 1.0 mil DFT (no loss) |
| Catalyst/Ratio            | N/A   |
| Reducer                   | N/A   |
| Retarder                  | N/A   |
| AirDry                    | N/A   |
| Oven Dry                  | N/A   |
| Shelf-Life (Unopened)     | 24 months   |
| Pot-Life (Catalyzed)      | N/A   |
| Recoat Instruction        | N/A   |
| PH                        | N/A   |
|                           |   |

#### DIRECTIONS

Shake well before using. Sand part on the lathe through the necessary, normal grit progression to level the surface before polishing, to at least 800 grit. Apply a small amount to a soft cloth or lint free paper towel and apply to the turning at a slow speed in an even end to end motion. Use a clean soft cloth or lint free paper towel to remove remaining residue. Repeat until desired gloss is achieved.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.