

Mohawk

Finishing Products, Inc.

Product Data Sheet

COLORED LACQUER ENAMEL

M104 – COLORS

AVAILABLE IN 13 OZ. AEROSOL

Product Description: The Mohawk opaque aerosol product line includes 14 colors, mostly black, whites, and off whites with some pastels with various sheens from flat to a super high gloss such as; M104-0225 Super High Gloss Black. These products do not need to be topcoated with a clear coat.

Advantages:

1. Easy to use.
2. Various colors available.
3. Complete coverage with a minimal number of coats.

Product Limitations:

1. For interior use only.

Colors Available:

| | | |
|-----------------------------|--------------------------|-----------------------|
| 0401 Almond | 0314 American Green | 1506 Provincial White |
| F224 Flat Black | 0416 Antique Ivory | F202 Flat White |
| S224 Satin Black | 0417 Light Antique Ivory | S202 Satin White |
| G224 Gloss Black | 0413 Antique Off-White | G202 Gloss White |
| 0225 Super High Gloss Black | 0412 Antique White | |

Characteristics:

*Weight per gallon: 7.47 – 7.83 lbs./gal.
Flashpoint: < 0 F/-17.8 c
Package Viscosity: 23-25 seconds #1 Zahn cup
Dry time: Air Dry @ 72 F, 35% relative humidity
To touch: 5 minutes
To handle: 15 minutes
To package: Overnight
Volatile Organic Compounds (VOC):
Does not exceed 95% VOC

*Spec. Gravity: .898 - .941
Boiling Range: -30 F/-34 c
*Non Volatile (wt): 15.0 – 19.2%
Package Life: 3 years

*Hazardous Air Pollutants: 0.45 ± 0.05 lb./1 lb. solids
Air Quality Data: Non-Photochemically Reactive

* Depending upon color

HMIS:

Health: 1
Flammability: 4
Reactivity: 0
Personal Protection: B

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface should be free of dirt, grease, etc. Use drop cloth or newspapers to protect surrounding areas from spray mist. For best results, use only when can temperature is between 65 °F and 90°F.

Spray on a test piece of wood. Use steady even strokes while spraying. Several thin coats give a better finish than one heavy coat. Allow coating to become tacky between coats.

For packaging or rubbing, allow at least overnight drying.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551