Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Wool-LubeTM Rubbing Lubricant

M720-135 (Paste Form), 136 (Liquid Form) Available in quarts and gallons (Paste form) Available in pints, gallons and 5 gallons (Liquid form)

Product Description: This Mohawk product used in conjunction with steel wool, abrasive pads, or wet-dry paper offers a smooth clear final appearance as a rubbing lubricant for all finishes. The velvet-satin luster will not haze.

Advantages:

1. Easy to use. 3. Wipes clean.

2. Will not gum up. 4. Can be lacquered over.

Product Limitations: None.

Characteristics:

Weight per gallon: 8.3 ± 0.1 lbs./gal. (Paste), Package Life: 2 years

 8.45 ± 0.1 lbs./gal (Liquid) Hazardous Air Pollutants: 0.0 lb./1 lb. solids Flashpoint: None observed Air Quality Data: Non-Photochemically Reactive

35 \pm 1.0% (Liquid) Personal Protection: B

Specifications:

Directions: Place a small amount of Mohawk Wool-LubeTM on a 3/0 or 4/0 steel wool pad soaked with water or a second method may be used – reduce liquid Wool-LubeTM 50/50 with water or to desired level in a container, then simply dip pad into solution. Rub surface in the direction of grain using smooth even strokes to obtain a uniform finish.

For fine satin sheens, wet rub with 400-600 sandpaper and Mohawk Wool-LubeTM. No polish is necessary after a Wool-LubeTM rubbing, simply wipe with a clean dry cloth. Wool-LubeTM is also available in paste form.

Safety Cautions: Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

See Material Safety Data Sheet (MSDS) for more information.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products Phone: 1-800-545-0047 Division of RPM Wood Finishes Group, Inc. Fax: 1-800-721-1545

P O Box 22000 Website: www.mohawk-finishing.com

Hickory, NC 28603